



SAFETY DATA SHEET

S.S.C. Stainless Steel Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	S.S.C. Stainless Steel Cleaner
Product number	A189 EV
Internal identification	Janitorial

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Neutral, cleaner for Stainless Steel.
------------------------	---------------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier

Evans Vanodine International
 Brierley Road
 Walton Summit
 Preston. UK. PR5 8AH
 Tel: 01772 322 200
 Fax: 01772 626 000
 qclab@evansvanodine.co.uk

1.4. Emergency telephone number

Emergency telephone	New Safety Data Sheets - 8.30am to 4.45pm - 01772 322 200 - Mon to Fri. (Also available 24/7 from our website www.evansvanodine.co.uk) Technical Advice - 8.30am to 4.45pm - 01772 318 818 - Mon to Fri
----------------------------	---

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 3 - H226
Health hazards	Eye Irrit. 2 - H319
Environmental hazards	Not Classified

2.2. Label elements

Pictogram



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.

S.S.C. Stainless Steel Cleaner

Precautionary statements	P102 Keep out of reach of children.
	P280 Wear eye protection.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233 Keep container tightly closed.
	P301 IF SWALLOWED:
	P313 Get medical advice/ attention.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
	P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
	P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/ container in accordance with local regulations.	

Contains PROPAN-2-OL

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PROPAN-2-OL		10-15%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-xxxx
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
2-BUTOXYETHANOL		1-3%
CAS number: 111-76-2	EC number: 203-905-0	
Classification		
Acute Tox. 4 - H302		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Do not induce vomiting. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Wash with plenty of water.

S.S.C. Stainless Steel Cleaner

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation No specific symptoms known.

Ingestion No specific symptoms known. But - May cause discomfort if swallowed.

Skin contact No specific symptoms known. But prolonged or excessively repeated skin contact could lead to removal of natural oils from skin.

Eye contact May cause temporary eye irritation. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Irritating gases or vapours. May explode when heated or when exposed to flames or sparks.

5.3. Advice for firefighters

Special protective equipment for firefighters Keep containers cool by spraying with water to reduce explosion risks. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with eyes.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Flush away spillage with plenty of water. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Eliminate all sources of ignition. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

S.S.C. Stainless Steel Cleaner

Storage precautions	Keep away from heat, sparks and open flame.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	See Product Information Sheet & Label for detailed use of this product.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	This product must not be handled in a confined space without adequate ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific hand protection noted, but protection for the skin is advisable to prevent removal of natural oils from skin.
Other skin and body protection	None required.
Respiratory protection	Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear. Blue.
Odour	Faint Alcoholic.
pH	pH (concentrated solution): 7.00
Melting point	-5°C
Initial boiling point and range	85°C @ 760 mm Hg
Flash point	35°C . Measured using test method, PMCC (Pensky-Martens closed cup).
Relative density	0.980 @ 20°C

S.S.C. Stainless Steel Cleaner

Solubility(ies) Soluble in water.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions See sections 10.1, 10.4 & 10.5

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects We have not carried out any animal testing for this product. Any ATE figures quoted below are from Toxicity Classifications that have been carried out using ATE (Acute Toxicity Estimate) Calculation Method using LD50 or ATE figures provided by the Raw Material Manufacturer.

Other health effects Low oral toxicity, but ingestion may cause irritation of the gastro-intestinal tract.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 43,333.77

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 33,367.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 336.67

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

S.S.C. Stainless Steel Cleaner

Toxicity We have not carried out any Aquatic testing, therefore we have no Aquatic Toxicity Data specifically for this product. The Aquatic Toxicity Data, where provided by the raw material manufacturer for ingredients with aquatic toxicity, can be made available on request.

12.2. Persistence and degradability

Persistence and degradability This product, at use dilutions, is readily broken down in biological effluent treatment plants.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Small amounts (less than 5 Litres) of unwanted product may be flushed with water to sewer. Larger volumes must be sent for disposal by approved waste contractor. Consign empty container to normal waste.

SECTION 14: Transport information

Road transport notes Please note : Product in pack size of 5 Litres or less is classed as a "Limited Quantity" for Transport and so will have the white with black points Transport hazard diamond. Pack size greater than 5 litres will have the red Flammable Liquid UN1987 Transport hazard diamond.

14.1. UN number

UN No. (ADR/RID) 1987

UN No. (IMDG) 1987

UN No. (ICAO) 1987

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ALCOHOLS, N.O.S. (isopropanol)

Proper shipping name (IMDG) ALCOHOLS, N.O.S. (isopropanol)

Proper shipping name (ICAO) ALCOHOLS, N.O.S. (isopropanol)

14.3. Transport hazard class(es)

ADR/RID class Class 3: Flammable liquids.

ADR/RID label 3

IMDG class Class 3: Flammable liquids.

ICAO class/division Class 3: Flammable liquids.

S.S.C. Stainless Steel Cleaner

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-D
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not relevant. for a packaged product.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Safety Data Sheet prepared in accordance with REACH Commission Regulation (EU) No 2015/830 (which amends Regulation (EC) No 453/2010 & 1907/2006). The product is as classified under GHS/CLP- Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures. Ingredients are listed with classification under GHS/CLP - Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.
----------------	---

15.2. Chemical safety assessment

No chemical safety assessment has been carried out as not applicable as this product is a mixture.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. IMDG: International Maritime Dangerous Goods. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. GHS: Globally Harmonized System.
--	---

S.S.C. Stainless Steel Cleaner

Classification abbreviations and acronyms	Acute Tox. = Acute toxicity Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Skin Irrit. = Skin irritation STOT SE = Specific target organ toxicity-single exposure
Key literature references and sources for data	Material Safety Data Sheet, Miscellaneous manufacturers. CLP Class - Table 3.1 List of harmonised classification and labeling of hazardous substances. ECHA - C&L Inventory database.
Classification procedures according to Regulation (EC) 1272/2008	Calculation Method.
Revision comments	Safety Data Sheet amended in accordance with REACH Commission Regulation (EU) No 2015/830 amendment. (Changes to Sections 2,3,15&16)
Revision date	01/06/2018
Revision	7
SDS status	The Hazard Statements listed below in this Section No 16 relate to the Raw Materials (Ingredients) in the Product (as listed in Section 3) and NOT the product itself. For the Hazard Statements relating to this Product see Section 2.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.