

SAFETY DATA SHEET

STAINLESS STEEL POLISH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STAINLESS STEEL POLISH
Product number K050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Stainless Steel cleaner

1.3. Details of the supplier of the safety data sheet

Supplier **SELDEN RESEARCH LIMITED**
STADEN LANE
BUXTON
DERBYSHIRE
SK17 9RZ
UNITED KINGDOM

Tel. 01298 26226
Fax. 01298 26540
email safety@selden.co.uk

1.4. Emergency telephone number

National emergency telephone number Mon to Fri 8.30am to 5.00pm - 01298 26226

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Aerosol 1 - H222, H229

Health hazards

Elicitation - EUH208

Environmental hazards

Not Classified

Classification (67/548/EEC or 1999/45/EC)

F+;R12.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

Precautionary statements

STAINLESS STEEL POLISH

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P102 Keep out of reach of children.

2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ALIPHATIC DISTILLATE	10-30%
CAS number: 64742-48-9 EC number: 265-150-3	
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R66.
BUTANE	5-10%
CAS number: 106-97-8 EC number: 203-448-7	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12
HYDROTREATED MINERAL OIL	1-5%
CAS number: 8042-47-5 EC number: 232-455-8	
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) -
METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6	<1%
CAS number: 55965-84-9 EC number: 611-341-5	
M factor (Acute) = 10 M factor (Chronic) = 1	
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) T;R23/24/25 C;R34 R43 N;R50/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

STAINLESS STEEL POLISH

General information

Treat symptomatically.

Inhalation

Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately. For breathing difficulties oxygen may be necessary.

Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.

Ingestion

Causes chemical burns to mouth, throat and stomach. May cause stomach pain or vomiting.

Skin contact

No specific symptoms known.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions

STAINLESS STEEL POLISH

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

See product label for detailed usage and instructions.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eye protection not normally required with day to day use of product

Hand protection

Use protective gloves.

Other skin and body protection

General workwear only

Hygiene measures

STAINLESS STEEL POLISH

DO NOT SMOKE IN WORK AREA!

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour

White.

Flash point

- 74°C N/A.

Upper/lower flammability or explosive limits

: 1.8

Relative density

0.82 @ @ 20 C°C

Auto-ignition temperature

+ 405°C

Comments

Information given relates to total aerosol container contents.

9.2. Other information

Other information

None.

SECTION 10: Stability and reactivity

10.1. Reactivity

May react with other cleaning chemicals. For specific reactions refer to Section 10.5

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects

No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.

Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.

Ingestion

May cause burns in mucous membranes, throat, oesophagus and stomach. May cause stomach pain or vomiting.

Skin contact

STAINLESS STEEL POLISH

No specific health hazards known.

Eye contact

Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity

Not classed as Hazardous to the Environment but release to the environment should be avoided.

12.1. Toxicity

Aquatic toxicity has not been carried out on this product. Data for raw materials contained in this product, when available, can be provided when necessary.

12.2. Persistence and degradability

Persistence and degradability

The product is biodegradable.

12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE
Proper shipping name (ADN)	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class	2	Class Code:5F	Label: 2.1
IMDG class	2.1		
ICAO class/division	2.1		

STAINLESS STEEL POLISH

14.4. Packing group

Not applicable.

IMDG packing group N/A

ICAO packing group N/A

14.5. Environmental hazards

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

EU legislation

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture.

SECTION 16: Other information

General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision date 09/01/2015

Revision 9

Risk phrases in full

R10 Flammable.

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Hazard statements in full

STAINLESS STEEL POLISH

EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.