

SAFETY DATA SHEET

STAINLESS STEEL CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STAINLESS STEEL CLEANER

Product number K042A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Stainless Steel cleaner

1.3. Details of the supplier of the safety data sheet

Supplier **SELDEN RESEARCH LIMITED**
STADEN LANE
BUXTON
DERBYSHIRE
SK17 9RZ
UNITED KINGDOM

Tel. 01298 26226
Fax. 01298 26540
email safety@selden.co.uk

1.4. Emergency telephone number

National emergency telephone number Mon to Fri 8.30am to 5.00pm - 01298 26226

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Aerosol 1 - H222, H229

Health hazards

Not Classified

Environmental hazards

Aquatic Chronic 4 - H413

Classification (67/548/EEC or 1999/45/EC)

F+;R12. R53.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H413 May cause long lasting harmful effects to aquatic life.
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated

Precautionary statements

STAINLESS STEEL CLEANER

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ISOPARAFFINIC HYDROCARBONS	30-60%
CAS number: — EC number: 923-037-2 REACH registration number: 01-2119471991-29-0000	
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 Aquatic Chronic 4 - H413	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R53,R66.
HYDROTREATED MINERAL OIL	30-60%
CAS number: 8042-47-5 EC number: 232-455-8	
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) -
BUTANE	10-30%
CAS number: 106-97-8 EC number: 203-448-7	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12
KEROSENE - NARROW CUT - NON AROMATIC	1-5%
CAS number: 64742-47-8 EC number: —	
Classification Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R66.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately. For breathing difficulties oxygen may be necessary.

Ingestion

Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

STAINLESS STEEL CLEANER

Eye contact

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

STAINLESS STEEL CLEANER

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

See product label for detailed usage and instructions.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eye protection not normally required with day to day use of product

Hand protection

Use protective gloves.

Other skin and body protection

General workwear only

Hygiene measures

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Flash point

- 74°C

Upper/lower flammability or explosive limits

: 1.8

Auto-ignition temperature

+ 405°C

STAINLESS STEEL CLEANER

Comments

Information given relates to total aerosol container contents.

9.2. Other information

Other information

None.

SECTION 10: Stability and reactivity

10.1. Reactivity

May react with other cleaning chemicals. For specific reactions refer to Section 10.5

10.2. Chemical stability

Stability

Stable at normal ambient temperatures. Avoid the following conditions: Shocks and physical damage.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects

No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Ingestion

May cause burns in mucous membranes, throat, oesophagus and stomach. May cause stomach pain or vomiting.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.

Eye contact

May cause severe eye irritation.

SECTION 12: Ecological Information

Ecotoxicity

May cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Aquatic toxicity has not been carried out on this product. Data for raw materials contained in this product, when available, can be provided when necessary.

12.2. Persistence and degradability

Persistence and degradability

The surfactants contained within the product comply with the biodegradability criteria as laid down in Regulation (EC) No 648/2004.

12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

STAINLESS STEEL CLEANER

12.4. Mobility in soil

Mobility

The product contains substances, which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE
Proper shipping name (ADN)	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class	2
IMDG class	2.1
ICAO class/division	2.1

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

Tunnel restriction code	(D)
-------------------------	-----

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

EU legislation

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and

STAINLESS STEEL CLEANER

mixtures (as amended).

Guidance

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture.

SECTION 16: Other information

General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision date 02/06/2013

Revision 3

Risk phrases in full

R10 Flammable.
R12 Extremely flammable.
R53 May cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.